

GoCardless

Table of Contents


- 1 About GoCardless
- 2 Installing GoCardless
- 3 Creating Access Tokens and Webhooks
 - 3.1 Creating an Access Token
 - 3.2 Creating a Webhook
- 4 Configuration for Non-Apache Servers
- 5 Common Issues

About GoCardless

GoCardless is the easy way to collect Direct Debit. Already serving more than 30000 businesses, perfect for recurring billing and B2B invoicing. [Learn more about GoCardless on their website at https://www.gocardless.com](https://www.gocardless.com).

Installing GoCardless

To install the GoCardless payment gateway, visit [Settings] > [Company] > [Payment Gateways] > Available, and click the "Install" button for GoCardless.



A message will be displayed, indicating that the payment gateway was successfully installed.

The gateway was successfully installed.

Manage GoCardless

Gateway Options

Access Token

Webhook Secret

Payment Options

☒ One time and subscription payments when possible ☐ One time payments only ☐ Subscription payments only

☐ Developer Mode [?](#)

GoCardless Webhook

Before you start using this gateway you must configure the following url as a Webhook in your GoCardless account.
`http://blesta.domain.com/callback/gw/6/gocardless/`

Accepted Currencies

☐ AUD
☐ GBP

☐ DKK - [add currency](#)
☐ NZD - [add currency](#)

☐ EUR
☐ SEK - [add currency](#)

Update Settings

Enter the details provided by GoCardless.

Option	Description
Access Token	Enter the Access Token that you created in your GoCardless Account. More details on creating this below.
Webhook Secret	Enter the Webhook Secret that you created in your GoCardless Account. More details on creating this below.
Payment Options	Payment Options allow you to accept one time or subscription payments. The following options are available: • One time and subscription payments when possible • One time payments only • Subscription payments only We recommend "One time and subscription payments when possible".
GoCardless Webhook	This is the URL you should point your Webhook to in your GoCardless Account when creating a Webhook.
Accepted Currencies	Check the currencies that you would like to be processed through this payment gateway. The following currencies are available: AUD, GBP, USD, CAD, DKK, NZD, EUR, SEK

When finished, click "Update Settings" to save the details. You have successfully installed and configured GoCardless!

Creating Access Tokens and Webhooks

To create an access token and webhook, log into your GoCardless account. Click "Developers" on the left, then the "Create" menu. Add an Access Token, then a Webhook. **Your Webhook should be at least 40 characters.**

You're currently in sandbox (testing) mode. You can [create a live account](#) or [sign in to your existing one](#).

GOCARDLESS

Home

Customers

Payments

Plans

Payouts

Events

Developers

Developers

Partners

Search

Settings

Developers

Get started

Read our API docs

Send test webhook

Simulate a scenario

Create

Looking to build a partner integration?

Please visit our Partners section, by clicking on the 'Partners' link above.

Access tokens

blesta

Read write

created 29.08.18

Publishable access tokens

Access token

Publishable access token

Webhook endpoint

Creating an Access Token

Create access token

You should only create an access token if you want to use your own account with the API.

If you want to build a [partner integration](#) to manage other users' accounts, you should [create an app](#) .

Name *

Scope

☒ Read only access

☐ Read-write access

Back

Create access token

1. Enter a Name, like "Blesta"
2. Select "Read-write access" for scope

3. Copy and save the Access Token that is generated by GoCardless and enter it into Blesta

Creating a Webhook

Create webhook endpoint

Name *

URL *

https://example.com

Secret

☐ Webhook client certificate ?

Back

Create webhook endpoint

1. Enter a name like "Blesta"
2. Enter the Webhook API as shown in Blesta
3. Enter a Secret that is **at least 40 characters in length**, and save in Blesta.

Configuration for Non-Apache Servers

GoCardless uses a non-standard header in its webhook callbacks. In order to make sure that the header is available so that you can successfully process the webhook, you will need to modify your .htaccess file and add:

```
RewriteEngine On
RewriteRule .* - [e=HTTP_WEBHOOK_SIGNATURE:%{HTTP:Webhook-Signature}]
```

Common Issues

Problem: A customer made a payment, and it's stuck in "Pending" status.

Solution: It can take up to 5 days for the bank transfer to complete successfully. Once that has happened, the status will be updated from "Pending" to "Active".

Problem: I get the error "You must enter a valid Webhook Secret."

Answer: Make sure your Webhook Secret is at least 40 characters long.